

Halo-Guard® FG-2

PRODUCT DESCRIPTION:

JAX Halo-Guard FG-2 grease can satisfy the lubricant demands in nearly any food plant machinery application. This makes JAX Halo-Guard FG-2 the ideal grease for general plant-wide grease lubrication. Superior water resistance, excellent compatibility with other greases, outstanding corrosion control, and excellent antiwear and E.P. performance help simplify grease inventory and provide the ultimate in food-grade grease performance.

APPLICATION:

Water resistance is of particular importance in food-grade grease applications. Few industrial applications are subject to the severe process and sanitation water and chemical contamination inherent in modern food and beverage plants. JAX Halo-Guard FG-2 is one of the most water-resistant food-grade greases on the market. This product benefits greatly from the easy-to-apply convenience of an aerosol package. The handy extension tube makes hard-to-reach applications easy.

Use on:

- Casters on carts and racks
- Circular cutting and trimming tools
- Blades of sharpened grinders and cutters
- Slow moving chains needing high water resistance

TECHNICAL DATA:

Propellant:	Propane, Butane
Flash Point:	Extremely Flammable
Spray Pattern:	Medium Stream
Viscosity:	95 @ 40°CSt (Base Fluid of Grease), typical
Texture:	Thick Wet Grease
Appearance:	Tan
Consistency:	Heavy
Specific Gravity:	0.95 - 1.05 @ 20°C for Concentrate

AEROSOL PACKAGING:

11 oz. net weight aerosol cans (12/case) – Part # JAX213

BULK PACKAGING:

15 oz. net weight grease gun tubes (50/case) and 35-pound pails – Part # HLG02





NSF International / Nonfood Compounds Registration Program

October 31, 2003

Patty Riek
PRESSURE-LUBE, INC. JAX
W134 N5373 CAMPBELL DRIVE
MENOMONEE FALLS, WI 53051
UNITED STATES

RE JAX HALO-GUARD FG-2 (AEROSOL)
Category Code: H1
NSF Registration No. 131601

Dear Patty Riek:

NSF has processed the application for Registration of **JAX HALO-GUARD FG-2 (AEROSOL)** to the *NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds* (2003), which are available at www.nsf.org/usda. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (<http://www.nsf.org/usda>). The NSF Registration Mark can be downloaded from the NSF website, at http://www.nsf.org/mark/download_marks.html.

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at <http://www.nsf.org/usda>. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti
NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants