

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 14D THREAD SEALANT WITH PTFE 16 FL.OZ.
Item No: 80633
Product Type: Sealant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH TLV: TWA	OSHA PEL:
ETHANOL 64-17-5	20-40	1000 ppm; STEL 1000 ppm	1000 ppm TWA; 1900 mg/m ³ TWA
TALC 14807-96-6	20-40	2 mg/m ³ respir. dust TWA	20 mppcf TWA
CASTOR OIL 8001-79-4	20-40	Not Listed	Not Listed
POLYVINYL RESIN 63148-65-2	5-20	Not Listed	Not Listed
2-PROPANOL 67-63-0	<5	200 ppm TWA	400 ppm TWA; 980 mg/m ³ TWA
TITANIUM DIOXIDE 13463-67-7	<3	10 mg/m ³ TWA ACGIH	15 mg/m ³ TWA (total dust)
METHANOL 67-56-1	<3	200 ppm TWA; 262 mg/m ³ TWA	200 ppm TWA; 260 mg/m ³ TWA
POLYTETRAFLUOROETHYLENE 9002-84-0	<3	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Methanol may cause blindness or death if swallowed.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Overexposure may cause eye and skin redness.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ETHANOL 64-17-5	20-40		A4 - Not Classifiable as a Human Carcinogen	Group 1 (drinking alcohol); Vol. 44, pg 35, 1988
TALC 14807-96-6	20-40	male rat-some evidence, female rat-clear evidence, male mice-no evidence, female mice-no evidence	A4- Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987
2-PROPANOL 67-63-0	<5		A4 - Not classifiable as a human carcinogen	Group 3 Monograph 71, 1999; Supp.7, 1987; Monograph 15, 1977
TITANIUM DIOXIDE 13463-67-7	<3	male rat-negative, female rat-negative, male mice-negative, female mice-negative	A4	Group 2B; Vol 93,2006; Vol 47,1989
POLYTETRAFLUOROETHYLENE 9002-84-0	<3			Group 3 Supplement 7, 1987; Monograph 19, 1979

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

4. FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): 74°F TCC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion: Oxides of carbon, Fluoride compounds

Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat.

Lower Explosive Limit: 2.3

Upper Explosive Limit: 12.7

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Residues may be cleaned up with isopropyl alcohol.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

Handling: Avoid contact with skin and eyes. Do not inhale vapors. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses

Skin: Rubber or plastic gloves.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection: An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White paste

Odor: Alcoholic

Boiling Point: 180° F

pH: Does not apply

Solubility in Water: Partial

Specific Gravity: 1.06-1.10

VOC Content(Wt.%): 36.5%

Vapor Pressure: 33 mm Hg @ 68 degrees F.

Vapor Density (Air=1): 2.07

Evaporation Rate: 7.7 (ether = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: WILL NOT OCCUR.

Incompatibilities: Strong oxidizers

Conditions to Avoid: Keep away from heat, sparks and open flame. - No smoking

Hazardous Products of Combustion: Oxides of carbon, Fluoride compounds

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

Product Name: 14D THREAD SEALANT WITH PTFE 16
FL.OZ.

Item No: 80633

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Consumer Commodity (Not more than five liters)
Hazard Class: ORM-D
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/NA Number: ID 8000

IMDG

Proper Shipping: Adhesives containing flammable liquid, Limited Quantity
Hazard Class: Class 3 PGIII
UN Number: UN 1133

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

Methanol

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: October/23/2007
Revision Number: 1