



Material Safety Data Sheet

Version: 1.7
06/04/2007

GE14449 12C-CRTRG(1.1LBS-0.485KG) ACRYLIC CAULK

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Eules Plant
10950 S. Pipeline Rd
Eules TX 76040

Revised: 06/04/2007

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Acrylic Latex Caulk
Formula: Mixture

HMIS

Flammability: 0 Reactivity: 0 Health: 1 Prot. Equipm.:

NFPA

Flammability: 0 Reactivity: 0 Health: 1 Special Haz.:

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
1,2-Ethanediol	107-21-1	1 - 5 %
Stoddard Solvent	8052-41-3	1 - 5 %
Butyl benzyl phthalate	85-68-7	5 - 10 %
<u>B. NON-HAZARDOUS</u>		
Limestone	471-34-1	30 - 60 %
Water	7732-18-5	10 - 30 %
2-propenoic acid, polymer	52640-81-0	10 - 30 %
2-Propenoic acid, Butyl ester,- Polymer with Ethenyl Acetate	25067-01-0	5 - 10 %

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Irritating to eyes, respiratory system and skin. Harmful by inhalation, in contact with skin and if swallowed. May cause allergic skin reaction. May cause central nervous system depression. Refer to other MSDS sections for detailed information.

Form: solid

Color: white

Odor: Trace Ammonia

**GE14449 12C-CRTRG(1.1LBS-0.485KG)
ACRYLIC CAULK**

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed. Irritation of the mouth, throat, and stomach. May cause kidney damage. May cause headache, dizziness, nausea, vomiting, gastrointestinal irritation and central nervous system depression.

SKIN

May be absorbed through skin and produce effects as listed under "Ingestion". Can cause irritation and reddening of the skin.

INHALATION

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Can irritate mucous membranes and respiratory tract with coughing and shortness of breath. Avoid inhalation of vapour or mist.

EYES

Contact can cause severe irritation and conjunctivitis (redness and swelling).

MEDICAL CONDITIONS AGGRAVATED

Central nervous system disorders. Pre-existing skin or respiratory diseases. Kidney disorders

SUBCHRONIC (TARGET ORGAN)

Respiratory system; Kidney; Central nervous system

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Inhalation; Dermal; Eyes

4. FIRST AID MEASURES

INGESTION

Immediate medical attention is required. Do NOT induce vomiting. If victim is conscious, give 2-4 glasses of water.

SKIN

Wash off with soap and water. Remove and wash contaminated clothing before re-use. Get medical attention if irritation or symptoms from Section 3 develop. Flush skin with large amounts of water for at least 15 minutes until no evidence of chemical remains.

INHALATION

Get medical attention if irritation or symptoms from Section 3 develop. If not breathing, begin artificial respiration using a barrier device. Because of chemical properties, do not use mouth-to-mouth contact. Remove to fresh air.

**GE14449 12C-CRTRG(1.1LBS-0.485KG)
ACRYLIC CAULK**

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT:

METHOD: Unknown

IGNITION TEMPERATURE: Unknown

FLAMMABLE LIMITS IN AIR - LOWER (%): Unknown

FLAMMABLE LIMITS IN AIR - UPPER (%): Unknown

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Keep out of water supplies and sewers.

7. HANDLING AND STORAGE

STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Remove and wash contaminated clothing before re-use. Keep away from children. Keep container tightly closed. Keep container dry. Do not inhale vapors. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics. Store between 40 F and 120 F. Product releases formaldehyde during curing.

GE14449 12C-CRTRG(1.1LBS-0.485KG) ACRYLIC CAULK

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29 CFR 1910.134).

PROTECTIVE GLOVES

Neoprene

EYE AND FACE PROTECTION

Safety glasses with side-shields; Monogoggles.

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
1,2-Ethanediol	107-21-1	ACGIH, Ceiling	Aerosol. 100 mg/m ³
1,2-Ethanediol	107-21-1	ACGIH, Ceiling	Aerosol. 100 mg/m ³
Stoddard Solvent	8052-41-3	ACGIH, TWA	100 ppm
Stoddard Solvent	8052-41-3	OSHA Z1, PEL	500 ppm; 2,900 mg/m ³

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	100.00 °C; 212 °F
VAPOR PRESSURE (20 C) (MM HG):	Unknown
VAPOR DENSITY (AIR=1):	No data available
FREEZING POINT:	Unknown
MELTING POINT:	Unknown
PHYSICAL STATE:	solid
ODOR:	Trace Ammonia
COLOR:	white
EVAPORATION RATE (BUTYL ACETATE=1):	Unknown

**GE14449 12C-CRTRG(1.1LBS-0.485KG)
ACRYLIC CAULK**

SPECIFIC GRAVITY (WATER=1):	1.61
DENSITY:	Unknown
pH:	ca. 8.0
VOLATILE ORGANIC CONTENT (VOL):	34.20 %(m)
SOLUBILITY IN WATER (20 C):	Unknown
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Unknown
VOC EXCL. H2O & EXEMPTS (G/L):	60.90

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO₂); Carbon monoxide; Oxides of nitrogen.; Toxic monomer fumes.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

Unknown

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: Unknown

OTHER

No data available

SENSITIZATION

No data available

SKIN IRRITATION

No data available

**GE14449 12C-CRTRG(1.1LBS-0.485KG)
ACRYLIC CAULK**

EYE IRRITATION

No data available

MUTAGENICITY

Unknown

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGY

No data available

CHEMICAL FATE

No data available

DISTRIBUTION

No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

TSCA list	y (Positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	n (Negative listing)
Canada NDSL Inventory	n (Negative listing)
EU list of existing chemical substances	n (Negative listing)
Australia Inventory of Chemical Substances (AICS)	n (Negative listing)
Canada DSL Inventory	y (Positive listing)
Korea Existing Chemicals	n (Negative listing)

**GE14449 12C-CRTRG(1.1LBS-0.485KG)
ACRYLIC CAULK**

Inventory (KECI)
Japan Inventory of Existing & New Chemical Substances (ENCS) n (Negative listing)
China Inventory of Existing Chemical Substances n (Negative listing)
For inventories that are marked as quantity restricted or special cases, please contact GE.

US Regulatory Information

CERCLA		
<u>PRODUCT COMPOSITION</u>	<u>Chemical</u>	<u>CERCLA Reportable Quantity</u>

CLEAN AIR ACT

CLEAN WATER ACT

SARA SECTION 302

SARA (311,312) HAZARD CLASS
Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS
50-00-0, Formaldehyde79-06-1, Acrylamide108-05-4, Vinyl Acetate

Canadian Regulatory Information

WHMIS HAZARD CLASS

Other

SCHDLE B/HTSUS: 3214.10.00.10 Mastic based on rubber

ECCN: EAR99

CALIFORNIA PROPOSITION 65
Warning! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
7440-38-2, Arsenic. 7439-92-1, Lead. 50-00-0, Formaldehyde. 140-88-5, Ethyl Acrylate. 75-07-0, Acetaldehyde. 79-06-1, 2-Propenamide. 107-13-1, .

16. OTHER INFORMATION

OTHER
C = ceiling limit NEGL = negligible EST = estimated NF = none found NA = not

**GE14449 12C-CRTRG(1.1LBS-0.485KG)
ACRYLIC CAULK**

applicable UNKN = unknown NE = none established REC = recommended ND = none
determined V = recommended by vendor SKN = skin TS = trade secret R =
recommended MST = mist NT = not tested STEL = short term exposure limit ppm =
parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status
not required under 40 CFR part 720.30(h-2)., These data are offered in good faith as typical values
and not as product specifications. No warranty, either expressed or implied, is made. The
recommended industrial hygiene and safe handling procedures are believed to be generally
applicable. However, each user should review these recommendations in the specific context of the
intended use and determine whether they are appropriate.