

RED DEVIL INCORPORATED -- 100% SILICONE SEALANT, 0810 -- 8030-00N084566

=====
Product Identification
=====

Product ID:100% SILICONE SEALANT, 0810

MSDS Date:02/01/1996

FSC:8030

NIIN:00N084566

MSDS Number: CGTLC

=== Responsible Party ===

Company Name:RED DEVIL INCORPORATED

Address:ONE WEBB ST

City:PRYOR

State:OK

ZIP:74361

Country:US

Info Phone Num:918-825-5744

Emergency Phone Num:918-825-5744

CAGE:DO902

=== Contractor Identification ===

Company Name:RED DEVIL INCORPORATED

Address:WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74362

Country:US

CAGE:DO902

Company Name:RED DEVIL, INCORPORATED

Address:ONE WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74361

Country:US

Phone:918-825-5744

CAGE:23577

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA GEL; (SILICA (AS AMORPHOUS SILICA)

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 11%

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:ETHYLTRIAACETOXYSILANE

CAS:17689-77-9

Fraction by Wt: 2%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:SILANE, METHYLTRIAACETOXY-; (METHYLTRIAACETOXYSILANE)

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2%

OSHA PEL:10 PPM (MFR)
ACGIH TLV:10 PPM (MFR)

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE) (IN WHITE PRODUCT ONLY)
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 2%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt: >75%
OSHA PEL:N/K
ACGIH TLV:N/K

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE, NOSE AND THROAT IRRITATION.
POSSIBLE SKIN IRRITATION. INHALATION OF PARTICULATES UNLIKELY DUE
TO PRODUCT'S PHYSICAL STATE.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH W/LARGE AMOUNTS OF WATER, FOR AT LEAST
15 MINUTES, WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION IF
IRRITATION PERSISTS. SKIN:WIPE MATERIAL FROM SKIN W/CLOTH OR PAPER
TOWEL, THEN WASH EXPOSED AREA W/SOAP & WATER.GET MEDICAL HELP IF
IRRITATION PERSISTS. INHAL:MOVE VICTIM TO FRESH AIR. GET MEDICAL
HELP IF IRRIT PERSISTS. INGEST:CONTACT LOCAL POISON CONTROL CENTER
IMMED!

=====
===== Fire Fighting Measures =====

Flash Point:>200F,>93C
Extinguishing Media:CARBON DIOXIDE OR FOAM.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . NO SPECIAL PROCEDURES REQUIRED.
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT (SEE
SPECIAL PROTECTION INFORMATION SECTION). CLEAN UP W/ABSORBENT
MATERIAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLOSED CONTAINER IN DRY
AREA.
Other Precautions:OBSERVE LIMITS FOR ACETIC ACID, FORMED DURING CURING

ON EXPOSURE TO WATER OR HUMID AIR.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF OVEREXPOSURE, WEAR A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:LOCAL EXHAUST MAY BE NECESSARY UNDER SOME HANDLING OR USE CONDITIONS.

Protective Gloves:NEOPRENE OR OTHER CHEM RESISTANT GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA .

Work Hygienic Practices:DO NOT WEAR CONTACT LENSES WHILE SPRAYING THIS MATERIAL, AS ACETIC ACID VAPOR MAY BECOME TRAPPED UNDER LENSES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

=====
===== Physical/Chemical Properties =====

Vapor Density:>1

Spec Gravity:>1 (H*20=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:THICK LIQUID; SLIGHT VINEGAR ODOR.

Percent Volatiles by Volume:<5

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MOISTURE WILL RELEASE ACETIC ACID VAPOR.

Stability Condition to Avoid:AVOID EXTREME HEAT.

Hazardous Decomposition Products:SILICON DIOXIDE, CARBON MONOXIDE, CARBON DIOXIDE, TRACES OF FORMALDEHYDE.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.